

A wireless Industrial style wall mountable transmitter for indoor or outdoor applications.

Applications

- Under counter Panic button
- Nursing home Panic button
- Bathroom Panic button
- Shower Panic button
- Door release button
- Door bell button

Features

- Code-Hopping Encryption
- Weather-proof / Splash-proof housing
- Lithium battery CR2032
- 20,000 Activations
- Frequency stability controlled +/- 75KHz

Certifications

- ETSI EN300 220-V2.4.1
- ETSI EN301-489-3 V1.4.1
- ETSI EN301-489-1 V1.9.2
- IEC 60950-1:2005 + A1:2009
- ICASA: TA-2014/2621

Description	Order Code
Wall mount Transmitter 403MHz	WMTX_REV2
Wall mount Transmitter 433MHz	WMTX_ REV2_433
Spare WMTX Casing ABS	WM_ABS



Specifications

- Encryption: Code-Hopping
- Range: 100m (Open air)
- Frequencies: 403MHz / 433MHz
- Voltage Range: 2.2V to 4.5V DC
- Current on TX: +/-14mA
- Sleep mode: +/-400nano A
- Dimensions: (lxbxh) 71 x 31 x 28mm
- Gross Weight: 74 grams
- Operating Temp: -3°C to 65°C
- Warranty: 24 Months