# **Bus Line Alarm Panel Receiver**











## **Specifications:**

Encryption Type:.....Code-Hopping KeeLog®

Receiving Range open air:...150m

Frequencies available:......403.55 & 433.92MHz

Memory Capacity:.....32 Remotes

Voltage Range:.....9.8V to 16V DC

Box Dimensions:......77 x 50 x 21mm

Current Draw:.....11mA

Operating Temp.:....-7°C to 65°C

Warranty:.....5 Years

Release Date:.....June 2009

#### **Order Codes:**

1-Channel Receiver:.....BUSRX

BUSRX + 2 x 4Button Remotes in a kit......BUSRX\_KIT

### **Features:**

- ☐ Code-Hopping Encryption KeeLog®
- Compatible to the Premier Texecom Alarm Panel
- ☐ Crystal controlled front-end for less frequency error shift
- Programmed via the panels keypad
- Momentary, 1 & 3 Seconds, Relay closure times
- ☐ Latching Relay output selectable
- □ On-board buzzer sounds on "Activation" and in "Learn" modes
- ☐ Frequencies available are 403.55MHz and 433.92MHz
- 12V DC power input voltage range
- ☐ Compact designed PCB for installing in small places
- Communication plug-in cable supplied

#### **BUTTON FUNCTIONS EXPLAINED:**



Order code: Tx4 (4 Button remote)



